ACCUITATE ACCUITATE MANUFACTURING



The Tsugami SS26 Opposed Gang
Tool CNC Lathe is a rugged performer
capable of taking on deep cuts while
maintaining simultaneous machining on
the main and sub spindle. Tsugami's
unique Modular Tool Zone is a key
comonent of the SS series of Swiss
Type Lathes and allows easy
replacement of rotary tools, indexed
tool holders and turning tool
holders. The result? Faster set-up
and changeover times, greater
flecibility in scheduling long and
short part runs.

SUGAMI SS26

The SS26 Lathe's ability to use the main and sub spindle independently and simultaneously dramatically cuts cycle time as well. Overall, tool modularity, rugged construction and simultaneous machining capability transform the exceptional Swiss turn into a multi-faceted machine tool for long and short run small parts.

TSUGAMI SS26 FEATURES

Maximum Bar Stock	26 mm	Control	FANUC 32i-B
# Axes	7	Main Spindle Speed	200 – 10,000 rpm
Sliding Headstock / Guide Bushing	YES	Sub Spindle Speed	200 – 10,000 rpm
CONVERTIBLE: Run w/o Guide Bushing (chucker)	YES	Live Tool Speed	5,000 rpm
Max Length: with Guide Bushing	270 mm, 10.62"	Main Spindle Motor	3.7 / 5.5 kW
Max Length: w/o Guide Bushing	50 mm, 1.97"	Weight	7,495 lbs., 3,400 kg
# Tool Positions (std / max)	24 (standard)	Footprint: W x D x H	79.5" x 65.9" x 79.5"; 2,020 × 1,675 × 2,020 mm